



# CRN TECNOPART, S.A.

Sant Roc 30  
 08340 VILASSAR DE MAR (Barcelona)  
 Tel: 937 591 484 Fax: 937 591 547  
 e-mail: crn@crntp.com - www.crntecnopart.com



## EM PLUS 600 ELECTRONIC INDICATOR 74x32

- The V / I version has the icons to show temperature / humidity / pressure in addition to being able to offer any icon (neutral).
- All models manage an alarm threshold.
- All models besides having the Televis protocol (without RVD) also have the Modbus protocol.
- Compatible with Televis Go
- Programmable via UniCard and compatible with Device Manager



MODEL	CODE
EMPLUS 600 NTC/PTC 12 Vca/cc	EMP60D0350000
EMPLUS 600 NTC/PTC 12-24 Vca/cc	EMP60D0450000
EMPLUS 600 NTC/PTC 230 Vca	EMP60D0750000
EMPLUS 600 J/K PT100 12 Vca/cc	EMP60P0350000
EMPLUS 600 J/K PT100 12-24 Vca/cc	EMP60P0450000
EMPLUS 600 J/K PT100 230 Vca	EMP60P0750000
EMPLUS 600 V/I 12 Vca/cc	EMP60I0350000
EMPLUS 600 V/I 230 Vca	EMP60I0750000

	EM PLUS 600 NTC/PTC	EMPLUS 600 J/K PT100	EM PLUS 600 V/I
Disply Field	<ul style="list-style-type: none"> <li>• NTC probe: 50,0...110,0°C</li> <li>• PTC probe: -55,0...140,0°C</li> </ul>	<ul style="list-style-type: none"> <li>• Pt100 probe: -150...650°C</li> <li>• TCJ: probe -40...750°C</li> <li>• TCK probe: -40...1350 °C</li> </ul>	<ul style="list-style-type: none"> <li>• -99...100 *</li> <li>• -99,9...100,0 *</li> <li>• -999...1000 *</li> </ul>
Display	3 1/2 digits + sign		
Analog inputs	1 PTC or NTC *	1 PT100 / TCJ / TCK*	(0...1V,0...5V,0...10V,)* (0...20mA,4...20mA)*
Serial ports	TTL port for connection to CopyCard and Televis System (requires Bus Adapter 350)		
Digital outputs	1 SPDT 8(4)A 250Vac		
Range	de -55 a 140°C	de -150 a 1350 °C	de -1999 a 1999
Power supply	According to model		
Dimensions	74 x 32 x 59 mm		

\* Selectable by parameter

