



CRN TECNOPART, S.A.

Sant Roc 30
08340 VILASSAR DE MAR (Barcelona)
Tel 902 404 748 - 937 591 484 Fax 937 591 547
e-mail: crn@crntp.com http:// www.crntecnopart.com

EW-130.322E

KEYBOARDS KDE - KDW - KDT KEYBOARDS TO THE SERIES RTX / RTD / RTN



AVAILABLE MODELS

MODEL	CODE
KDE Plus	KDE400E004000
KDW Plus	KDW6004004080
KDT Plus	KDT6VBWF16080
ECHO Plus	EH000050V4000

The KD family devices are remote keyboards connected to a power unit for the management of all applications of compact equipment and refrigerators.

Three formats available cover all your needs:

Format KDT open: 87x135mm Keyboard with touch technology for refrigeration applications

Format KDE Plus: Panel keypad 32x74 for controllers for refrigerated cabinets

Format KDW Plus: Panel keypad 180x37 for controllers for refrigerated cabinets.

Interconnection cable with the base plate of different measures (see table).

TECHNICAL DATA

	KDE PLUS	KDW PLUS	KDT
Casing	PC+ABS UL94 V-0 resin casing, polycarbonate window, thermoplastic resin keys.	PC+ABS UL94 V-0 resin casing, polycarbonate window, thermoplastic resin keys.	Open plate
Dimensions	front 74 x 32mm, depth 30mm.	front 180 x 37mm, depth 23mm	front panel 87x135 mm panel thickness 15/10 mm
Mounting	panel mounting with 71x29 mm (+0.2/-0.1 mm) drilling template.	panel mounting with 150x31 mm (+0.2/-0.1 mm) drilling template.	front panel mounting can be set for a distance of up to 100mm drilling template: 67x120 mm
Display	3 digits + sign and 8 colour status icons decimal point *	3 digits + sign and 8 colour status icons decimal point *	3 digits + sign and 8 colour status icons decimal point *
Range	-55...140°C	-55...140°C	-55...140°C
Resolution	1 or 0,1°C	1 or 0,1°C	1 or 0,1°C
Power supply	from power board	from power board	from power board
Buzzer	optional	optional	optional
Number keys	4	6	6 capacitive touch keys
Connectors	JST for connection to ECHO display module (ECPlus)	JST for connection to ECHO display module (ECPlus)	JST for connection to ECHO display module (ECPlus)
IP rating	IP65	IP65	IP65

* selectable by parameter



NOTE:
You can connect an ECHO module (ECPlus) KDWPlus in the same terminal where connects the base.

