



CRN TECNOPART, S.A.

Sant Roc 30
08340 VILASSAR DE MAR (Barcelona)
Tel 902 404 748 - 937 591 484 Fax 937 591 547
e-mail: crn@crntp.com [http:// www.crntecnopart.com](http://www.crntecnopart.com)



ELECTRONIC PROGRAMMABLE TIMERS ELIWELL

SERIE EWTS PLUS 990 (Panel Mounting 32x74 mm)

Possibility to choose the type of computer (up or down), type of operation (monostable or bistable timer), developed and complete death rate of input and output functionality
Internal backup battery that keeps the data or continues with the computation in case of power failure
Operation ON / OFF and remote reset

MODEL	CODE	OUTPUT	INPUT	VOLTAGE
EWTS PLUS 990 12 V	237060993	2 Relay	2 Digitals inputs	12 V
EWTS PLUS 990 24V	237060995			24 V
EWTS PLUS 990 230 V	237060997			230 V



Display range:

9999 hours,
99 hours and 59 minutes,
99 minutes and 59 seconds,
99 seconds and 99 hundredths

TECHNICAL DATA

Front protection: IP65.

Housing: plastic body in resin PC + ABS UL94 V-0 polycarbonate display, keys in thermoplastic resin.

Dimensions: front 74x32 mm, depth 60 mm.

Installation: on panel, 71x29 mm mounting template (+0.2 / 0.1 mm).

Temperature: -5.55 ° C.

Storage temperature: 30 .. 085 ° C.

Humidity use and storage: 10.90% RH (non-condensing).

Digital inputs: 2 digital inputs configurable voltage free from parameter.

Serial Port: TTL Memory Card aconexión to TelevisSystem pair.

Digital outputs :

- first output SPDT relay 8 (3) A 250VA 1/2HP
- SPST relay second exit 8 (3) A 250VA 1/2HP

Accuracy: 3.6 sec / h

Consumption: 3 VA.

Outdoor rechargeable battery: power 9Vc, absorption instrument 9mA on battery power.

